


## A2L PRODUCT SOLUTIONS


Solutions for Cold Storage, Convenience Stores, Light Industrial, Retail Supermarkets, and Small Format Applications



OLP 6-Compressor with Integrated Microchannel 2-Fan Condenser (Outdoor)



3-Wide Vertical 6-Compressor (Indoor)



Levitor II (LY-A2L/LZ-A2L)



Microchannel (MW-A2L)




COMPACT RACK SYSTEMS	Protocol A2L	
	Outdoor Low Profile	Indoor (available Summer 2026)
Available Controllers	Copeland E3 and Site Supervisor Danfoss AK-SM 820A, AK-SM 850A, AK-SM 880A Micro Thermo MT-722G	
Capacity MBH (kW)	29-431 (9-126)	29-575 (9-169)
Compressors	SPO — 2-3 Copeland Scroll OLP — 2-6 Copeland Scroll	SPI — 2-3 Copeland Scroll 2-Wide Vertical — 2-4 Copeland Scroll 3-Wide Horizontal or Vertical — 2-6 Copeland Scroll 4-Wide Horizontal — 2-8 Copeland Scroll
Voltage V/ph/Hz	208/3/60 • 460/3/60 • 575/3/60	
Refrigerant Type	A2L (R-454A or R-454C)	

AIR-COOLED CONDENSERS	Remote Tube and Fin	Remote Microchannel
Fan Arrangement	1x1 through 2x7	2x1 through 2x7
Voltage	230/1/60 • 208-230/3/60 • 460/3/60 • 575/3/60	208-230/3/60 • 460/3/60 • 575/3/60
Refrigerant Type	A2L (R-454A, R-454B, or R-454C)	

CONDENSING UNITS	H-Series A2L High-Efficiency
Compressors	Copeland Scroll or Discus Bitzer Reciprocating
Voltage	208-230/1/60 • 208-230/3/60 • 380/3/50 • 460/3/60 • 575/3/60
Refrigerant Type	A2L (R-454A or R-454C)



Solutions for Convenience Stores, Retail Supermarkets, and Small Format Applications



EVAPORATORS (Ceiling-Mounted)	KR-A2L Low Profile	GH/GL-A2L Low Velocity Center Mount	LH-A2L Low Velocity Center Mount	MK/MV-A2L Medium Profile	MS-A2L Medium Profile
Application Temperature	Low/Medium	Medium	Low/Medium	Low/Medium	Low/Medium
Available Defrost Types	Air/Electric/Hot Gas	Air/Electric/Hot Gas	Air/Electric	Air/Electric/Hot Gas	Air/Electric/Hot Gas
Capacity MBH (kW)	4-34.8 (1.2-10.2)	3.5-41 (1-12)	3.3-18.7 (1-5.5)	8.2-64 (2.4-18.8)	15-113.2 (4.4-33.2)
Coil Discharge	Single	Dual	Dual	Single	Single
Motor Voltage V/ph/Hz	115/1/60 • 208-230/1/60	115/1/60 • 208-230/1/60	115/1/60 • 208-230/1/60	115/1/60 • 208-230/1/60 • 208-230/3/60 • 460/1/60 • 460/3/60	115/1/60 • 208-230/1/60 • 208-230/3/60
Refrigerant Type	A2L (R-454A or R-454C)				

Solutions for Cold Storage and Light Industrial Applications

More Information About A2L Refrigerants



Complete Krack Product Line Card



## A2L PRODUCT SOLUTIONS

### Solutions for Merchandising

In Q2 2026, Hussmann will begin introducing A2L compatible versions of all the popular remote merchandising solutions previously offered for use with higher GWP refrigerants. This expansive offering will become available through a staged releases in 2026, allowing for a more seamless transition to using A2L refrigerants in new stores as well as remodels and updates.

Available solutions will include the following (types and applications varying by line):

<b>Application Temperature</b>	Low and Medium Temperature	
<b>Case Configuration Types</b>	Reach-Ins	1-5 Door Standard and Narrow Depth, 4-5 Door Back-to-Backs, and End Cases
	Multi-Decks and Single-Decks	Doored and Open Self-Service Cases Including Wedges
		Straight and Curved Glass Service and Combination Service/Self-Service Cases
Coffin Cases	Solid or Glass-Front Islands Available Open or with Sliding Glass Lids	
<b>Product Applications</b>	Bakery • Beverage • Cheese • Dairy • Deli • Floral • Frozen Food • Ice Cream • Meat • Prepared Food • Produce • Seafood • Wine	
<b>Refrigerant Type</b>	A2L (R-454A or R-454C)	



**Impact® 5-Door  
Narrow Reach-In**



**Insight® 5-Door  
Standard Depth  
Reach-In**



**Insight® 12-Foot  
Multi-Deck with  
Ultra-Low Front  
and Doors**



**Isla 4-Sided  
Multi-Deck**



**Entyce 3-Level  
5' Wide Island**



**Insight® 12-Foot  
Open Multi-Deck**



**Q-Series Multi-Deck  
Meat/Fish Service  
Case with Vertical  
Glass**



**R3 Combination  
Service/Self-Service**



**Excel®  
Frozen Island**

**All Current  
Hussmann  
Display Cases**



**Hussmann  
Specialty  
Display Cases**

