

# MPC-ETN

Self-Service, Narrow Mobile Critical Temp Merchandiser for RPCs, Crates or Boxes

### Increase Product Shelf Life

Refrigerated merchandiser combined with dry Euro table display

# **Location Flexibility**

'Plug & Play' design with casters allow you to feature products any where in your store

# Increase Impulse Buys

Display bulk produce, cut fruit, berries, promo items, or meat

# **Extend Product Shelf Life**

Adjustable controls to set ideal temperatures based on products being merchandised

## Simple Temperature Adjustment


Easily change temperature by store personnel


# Reduction in Store Labor

Merchandise using RPCs or standard produce boxes



# Self-Service, Narrow Mobile Critical Temp Merchandiser for RPCs, Crates or Boxes







MPC-ETN-M-6S: 6' Self Contained

### Standard.

- R448a Regulatory-Compliant Low GWP Refrigerant condensing unit (self-contained)
- Evap pan (floor sink not required)
- Power cord NEMA plug (self-contained) Casters (self-contained)
- Danfoss controller with demand defrost (selfcontained) Solid end panels
- Black interior
- Painted exterior
- Energy efficient fans
- Adjustable telescopic wire rack

# Options.

- View end panels
- Exterior laminated finish
- Hand rail plex
- Hand rail PTM
- 6 level interior step display

**DOE 2017** 

Hussmann refrigerated merchandisers configured for sale for use in the United States meet or surpass the requirements of the DOE 2017 energy efficiency standards.

Some optional features may need to be certified by UL, NSF, and/or other 3rd party certification agencies. Contact Hussmann for verification or questions for availability.

NOTE: These merchandisers are designed for use in stores when temperature and humidity do not exceed  $75^{\circ}F$  and 55% R.H. Case is designed for holding pre-chilled product only.

We reserve the right to change or revise specifications and product design in connection with any feature of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions, or replacements for equipment previously sold or shipped.

For additional resources and warranties, contact your representative or visit





Note.

Intertek

Use Hussmann's technical data sheets to get precise dimensions for all store layout purposes.



# **Specifications**

Exterior							Electrical					A/C	Approx.
	Dimensions							Circuit	Fuse	NEMA	Load	Load	Ship Wt.
Model	L	D	Н	HP	Refrig.	Hz/Ph	Volts	Amps	Amps	Plug	(BTU/h)	(BTU/h)	(lbs)
MPC-ETN-M-6S	72"	49 7/8"	51 7/8"	3/4	R-448A	60/1	120	23.5	30	L5-30P	5880	8212	900
MPC-ETN-M-6S	72"	49 7/8"	51 7/8"	3/4	R-448A	60/1	240	16.3	30	L14-30P	5880	10553	900

<sup>\*</sup> Requires field wiring. Length dimensions are without optional bumpers.
\*\* Refrigeration load calculated at 20° F evaporation and 110° F condensing temperature.



# Hussmann

13770 Ramona Avenue Chino, California 91710-5423 Ph: 1-800.395.9229