HUSSMANN® Entyce Family of MERCHANDISERS







TYA3ECRC-S

Entyce Advantage Self-Contained, Island or End, Multi-Deck Merchandiser

















ADVANTAGES

Exceptional Merchandising

with open, cascading product presentation.

Designed To Guide Your Shopper Around To See

Around to see everything and inspire impulse buying.

More Packout

High pack out in small footprint.

New Adjustable Shelving System

Merchandising flexibility with vertical shelf height adjustments.

Product Temp Enhancement

Developed for more stringent ambient conditions - Balanced air distribution and advanced coil technology.



KEY POINTS

Energy Efficient

EcoShine ULTRA LED lighting increases energy efficiency

Shortened Lead Times

Product now built on standard assembly line



TYA3ECRC-S

Entyce Advantage Self-Contained, Island or End, Multi-Deck Merchandiser

















TYA3ECRC-5x7I-S

5'w x 7'L Island Self-Contained Merchandiser



TYA3ECRC-5x7I-S

5'w x 7'L Island Self-Contained Merchandiser



Technical Information.




Scan the QR code with your mobile device to access technical data sheets on hussmann.com

Lengths. (TYA3ECRC-5x7I-S) 5'W x 7'L Island (TYA3ECRC-3x5.5E-S) 3'W x 5.5'L End......

(TYA3ECRC-3x4.5E-S) 3'W x 4.5'L End.....


TYA3ECRC-3x5.5 or 4.5E-S

3'w x 5.5'L or 4.5'L Flat End Self-Contained Merchandiser



TYA3ECRC-3x5.5 or 4.5E-S

3'w x 5.5'L or 4.5'L Flat End Self-Contained Merchandise



STANDARD.

OPTIONS.

- Exterior top and

- Painted exterior 701 Shadow Black
- 2" black vinyl cart bumper
- Radius tempered glass perimeter
- EcoShine ULTRA 3500k LED canopy lights -5 year warrantv
- Energy efficient fan motors
- R448A Regulatory-compliant low GWP refrigerant condensing unit
- Evap pan-floor sink not required

- Exterior finish □ black

- Interior finish □ black

- Designed for use in stores when temperature and humidity do not exceed 75°F / 55% RH (Type 1), or 80°F / 55% RH (Type 2)

bumper retainer □ black

DOE 2017 Energy Efficiency Compli

Hussmann refrigerated merchandisers configured for sale for use in the United States meet or surpass the requirements



Interte

NOTE: The

responding changes, improvements, additions, or replacements for equipment previously sold or shipped.

For additional resources and warranties, contact your representative or visit www.hussmann.com.

of the DOE 2017 energy efficiency standards.	requirements	- 10" and 12" shelves					
Note. Use Hussmann's technical data sheets to get precise dimension for all store layout	1 1/1 - 30 P C 6 766 C	w PTM (5x7l)					
ek Intertek purposes.		location □ top mount					
	res when temperature and humidity do not exceed is designed for holding pre-chilled product only.	☐ bottom mount -Electrical connection wiring type ☐ hardwired					
	and product design in connection with any feature of	☐ cord and plug					

Exterior				Electrical				Refrig.**	A/C	Approx.			
	Dime	nsions		Nom.				Circuit	Fuse	NEMA Plug	Load	Load	Ship Wt.
Model	L	D	Н	HP	Refrig.	Hz/Ph	Volts	Amps	Amps	(optional)	(BTU/h)	(BTU/h)	(lbs
TYA3ECRC-5x7I-S	83.5"	57.5"	57.5"	3	R-448A	60 / 1	208	28.0	50	CS-6365-C	15470	26150	1100
TYA3ECRC-3x5.5E-S	68"	36.625"	57.5"	1 3/4	R-448A	60 / 1	208	21.7	30	L14-30P	11550	17950	900
TYA3ECRC-3x4.5E-S	54"	36.625"	57.5"	11/4	R-448A	60 / 1	208	17.6	30	L14-30P	9450	15065	800

^{**} Refrigeration load calculated at 20° F evaporation and 110° F condensing temperature.



Hussmann

13770 Ramona Avenue Chino, California 91710-5423 Ph: 1-800.395.9229

www.hussmann.com