

HUSSMANN®

SELF-CONTAINED MERCHANDISER SOLUTIONS

Impact®



RL-WE

SELF-CONTAINED BACK-TO-BACK REACH-IN MERCHANDISER



ADVANTAGES

- Ideal for any low temperature or frozen food products
- Environmentally-friendly R-290 natural refrigerant that has zero ozone depletion potential (ODP) and 3 Global Warming Potential (GWP)
- High pack-out in limited footprint allowing more product in the same space
- UL Listed, NSF Type II compliant, and DOE 2017 certified



KEY FEATURES

- The display area per door is identical to the capacity of the standard depth RL
- Reduces the footprint of standard back-to-back reach-in cases by 16 inches
- Available with Hussmann Innovator and Innovator III doors
- Merchandiser rejects heat through a continuous flow store level water-loop system that operates between 50° and 115° F inlet temperature
- EcoShine II LED customized for optimal product lighting and reduced maintenance costs
- Detachable fan plenums for easy-to-clean case bottom
- CoreLink™ controller enabled remote performance monitoring available

EVOLVE
R-290

microDS™



RLNI4W



1.800.592.2060



www.hussmann.com

RLNI-W Narrow Back-to-Back Reach-In Merchandiser



SERVICEABILITY

- Detachable fan plenums for easy-to-clean case bottom
- Remote performance monitoring available through CoreLink™ controller

SUSTAINABILITY

- EcoShine II LED customized for optimal product lighting and reduced maintenance costs
- Minimal environmental footprint with CO₂ ZERO Ozone Depletion and Global Warming Potential of 3

SPECIFICATIONS

Models	RLNI4W and RLNI5W
LED Lighting	mullion
Number of Display Levels	6
Power Connection	NEMA L21-20P (4-Dr) or L21-30P (5-Dr) <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <p>L21-20P</p>  </div> <div style="text-align: center;"> <p>L21-30P</p>  </div> </div>
Power Supply	208 VAC / 3-phase / 60 Hz
Refrigerant	R-290 (propane)

AVAILABLE OPTIONS

- Lift-out bottom rack
- Heavy-duty front panels and deck pans
- Additional display shelves available
- Bumpers (front and ends)
- Price tag molding
- Product stops
- Contour fascia
- Heavy-duty shelves


TECHNICAL INFORMATION



Scan QR code with your mobile device to access additional information at www.hussmann.com

Available with 4 or 5 doors per case.

DIMENSIONS



Dimensions	4-Door	5-Door
Length	122 3/4 (3,118)	153 1/4 (3,892)

NOTE Dimensions are in Inches (millimeters)

NOTE: Use Hussmann's technical data sheets to get dimensions for all store layout purposes.

NOTE: These merchandisers are designed for use in stores when temperature and humidity do not exceed 75° F (23.9° C) and 55% R.H.

We reserve the right to change or revise specifications and product design in connection with any feature of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions, or replacements for equipment previously sold or shipped. For additional resources, contact your representative or visit www.hussmann.com.

©2024 Hussmann Corporation

HUSSmann®

Hussmann Corporation
12999 St. Charles Rock Rd.
Bridgeton, MO 63044-2483
Ph: 1.800.592.2060

www.hussmann.com

PS_RLNI-W_0000440_D_EN