







Hussmann refrigerated merchandisers configured for sale for use in the United States meet or surpass the requirements of the DOE 2017 energy efficiency standards.

SELF-SERVICE NON-CRITICAL TEMP PRODUCE REMOTE

## MPC 3x6, MPC 6x6-Side B Self-Service Produce Display







## REFRIGERATION DATA:

		CAPACITY *** (BTU/HR/FT)	TEMPERAT			
CASE LENGTHS	CASE USAGE*	RATING CONDITION	EVAPORATOR	DISCHARGE	VELOCITY (FT/MIN)	
		AHRI 1200	AHRI 1200	AIR ** (°F)		
3X6	NON-CRITICAL PRODUCE	705	22	34~36	130~180	

CASE LENGTHS	EST. REFG.	20°F GLYCOL 6° RISE				
LENGTHS	CHRG. (LBS)	GPM	PSI			
3X6	1.8	N/A	N/A			

- \*APROVED FOR NON-CRITICAL TEMP PRODUCE ONLY.
- \*\*DISCHARGE AIR MEASURED AT UPPER SECTION OUTLETS.
- \*\*\*REFRIGERATION NOTES:
  - 1) AHRI 1200 RATING POINT FOR ENERGY CONSUMPTION COMPARISON ONLY
  - 2) USE DEW POINT FOR HIGH GLIDE REFRIGERANTS. CARE SHOULD BE TAKEN TO USE THE DEW POINT IN P/T TABLES FOR MEASURING AND ADJUSTING SUPERHEAT. ADJUST EVAPORATOR PRESSURE AS NEEDED TO MAINTAIN THE DISCHARGE AIR TEMPERATURE SHOWN.
  - 3) RATING CONDITION IS NSF TYPE I, 75°F/55% RH

## **REFRIGERATION DATA CONTINUED:**

ELEC. THERM SENSOR S		DEFROST	TIME	DEFROST	TERM. TEMP	DRIP	DEFROST		
USAGE	CUT IN (°F)	CUT OUT (°F)	TYPE	(MIN)	FREQUENCY (#/DAY)	(°F) COIL ONLY	TIME	WATER (LBS/DAY/FT)	
PRODUCE	32	29	OFF TIME	30	6	48	N/A	1.0	

## **ELECTRICAL DATA:**

CASE LENGTH		EVAPORATOR FANS					CANOPY LIGHTS OPTIONAL LED SHELF LIGHTS		MAX. LED LOAD (W/ ALL OPTIONS)		ANTI-SWEAT HEATERS (ON FAN CIRCUIT)		CONVENIENCE OUTLETS (OPTIONAL)			
	# OF EVAP FANS	BLADE DIA. (IN.)	BLADE PITCH (°)	AMPS	WATTS	AMPS	WATTS	AMPS	WATTS	AMPS	WATTS	AMPS	WATTS	# OUTLETS	VOLTS	AMPS
3X6	1	6.7	25	0.12	8	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A