




Intertek



Intertek

Standard field electrical connections are at the top left of the merchandiser



*Coils, fans and TXVs are modular with one per 3 or 4 foot section.

Portion of parts removed for clarity.

12 foot merchandiser shown.



WARNING

The SD6 display cases with doors must be securely anchored to the floor, wall, or back-to-back case during the installation in accordance with the installation manual. Failure to follow such instructions may result in serious injury or death.

IMPORTANT

ONE FLOOR DRAIN IS RECOMMENDED FOR EACH CASE.

NSF Certification

This merchandiser model is manufactured to meet NSF/ANSI (National Sanitation Foundation) Standard #7 requirements for construction, materials and cleanability.

Performance Data	Page 2	Estimated Shipping Weights	Page 6
Product Data (AHRI Statistics)	Page 2	Shelf Options	Page 6
Cross Section	Page 3	Wiring Diagrams	Page 7
Plan View	Page 4	QR Code for Parts and Product Information	Page 10
Electrical & Lighting	Page 5	Revision History	Page 10

Data sheet-S-Series SD6N

We reserve the right to change or revise specifications and product design in connection with any feature of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions or replacements for equipment previously sold or shipped.

S-Series SD6N
Dairy / Deli / Beverage /
Produce / Meat

Refrigeration Data ¹

SD6N		Optimal Shelf Life			Energy Comparison
Application		Dairy/Deli/ Beverage/ Produce	Convertible/ Meat ³	NSF Type 2 Ambient ³	AHRI 1200 Rating Point ⁴
Temperature	Discharge Air °F (°C)	39 (3.9)	38 (3.3)	39 (3.9)	39 (3.9)
	Average Evaporator °F (°C) ²	33 (0.6)	32 (0.0)	32 (0.0)	33 (0.6)
Refrigeration Load	Parallel Btu/hr/ft (Watts/m) ⁵	246 (237)	246 (237)	323 (311)	246 (237)
	Conventional Btu/hr/ft (Watts/m) ⁵	255 (245)	255 (245)	335 (322)	255 (245)

Notes:

1. All data based on store temperature and humidity that does not exceed NSF Type 1 ambient conditions of 75°F and 55% relative humidity, except where noted.
2. Average evaporator temperature shown. Use dew point for high glide refrigerants for unit sizing. Care should be taken to use the dew point in PT tables for measuring and adjusting superheat. Adjust evaporator pressure as needed to maintain discharge air temperature shown.
3. Data for operation in NSF Type 2 ambient of 80°F and 55% relative humidity.
4. AHRI 1200 Rating Point for energy consumption comparison only.
5. Add 10 Btu/hr/ft (9.6 Watts/m) for optional LED mullion light fixtures.

Defrost Data

Frequency (hours between defrost) 24

Defrost Water ⁷ 1.0 lb/ft/day
(0.45 kg/m)

⁷ (± 15% based on case configuration and product loading).

OFFTIME
Time (minutes) 50

ELECTRIC OR GAS Not Available

Conventional Controls

Low Pressure Backup Control CI/CO ⁶
35°F /25°F
1.7°C / -3.9°C

Indoor Unit Only, Pressure Defrost Termination ⁶
40°F (4.4°C)

⁶ Use a Temperature Pressure Chart to determine PSIG conversions.

Estimated Charge ⁷

4 ft	1.9 lb	30 oz	0.9 kg
6 ft	2.8 lb	45 oz	1.3 kg
8 ft	3.7 lb	59 oz	1.7 kg
12 ft	5.1 lb	82 oz	2.3 kg

⁷ This is an average for all refrigerant types. Actual refrigerant charge may vary by approximately half a pound.

Product Data

Gross Refrigerated Volume ⁸ (Cu Ft/Ft) 5.8 ft³/ft (0.54 m³/m)
AHRI Total Display Area ⁹ (Sq Ft/Ft) 5.1 ft²/ft (1.55 m²/m)
Shelf Area ¹⁰ (Sq Ft/Ft) 6.2 ft²/ft (1.89 m²/m)

⁸ AHRI Gross Refrigerated Volume: Refrigerated Volume/Unit of Length, ft³/ft [m³/m]

⁹ Computed using AHRI 1200 standard methodology: Total Display Area, ft² [m²]/Unit of Length, ft [m]

¹⁰ Shelf surface area is composed of bottom deck plus standard shelf complement for this model: (5) rows of 12 in. shelves distributed evenly.

S-Series Multideck Merchandiser with EcoVision Doors,
6 Display Levels, Narrow Bottom, Standard Height Front

S-Series SD6N
Dairy / Deli / Beverage /
Produce / Meat

DOE 2017
Energy Efficiency
Compliant


Husmann refrigerated merchandisers configured for sale for use in the United States meet or surpass the requirements of the DOE 2017 energy efficiency standards.

Shelf complement shown as tested.
Five rows of 12 inch shelves spaced
equally between bottom display pan
and interior top panel.


SD6N

Dimensions shown as in. and (mm).

Other optional kits (top piping
and vent fans) add to the overall
case height.



Dimensions shown as in. and (mm).



(12 Foot Model shown above)

	4 ft	6 ft	8 ft	12 ft
General				
(A) Case Length (without ends or partitions) (Each end and insulated partition adds 1 1/2 in. (38 mm) to case line up.)	48 3/8 (1229)	72 3/8 (1838)	96 3/8 (2448)	144 1/2 (3670)
Maximum O/S dimension of case back to front (includes bumper)	26 1/4 (667)	26 1/4 (667)	26 1/4 (667)	26 1/4 (667)
(B) Distance between edges of external legs and center legs	NA	29 (737)	41 1/2 (1054)	41 1/2 (1054)
(C) Distance between edges of center legs	43 3/4 (111)	NA	NA	43 3/4 (111)
Electrical Service (Field Electrical Wiring Connection)				
(D) LH End of case to center of Field Electrical Wiring Connection (top of case)	14 3/8 (365)	14 3/8 (365)	14 3/8 (365)	14 3/8 (365)
Back of case to center of Field Electrical Wiring Connection	3 1/4 (651)	3 1/4 (651)	3 1/4 (651)	3 1/4 (651)
Waste Outlets				
(E) RH End of case to the center of right waste outlet	12 (305)	12 (305)	12 (305)	12 (305)
(F) RH End of case to the center of left waste outlet	36 1/4 (921)	60 1/4 (1530)	84 1/4 (2140)	132 3/8 (3362)
Back O/S of case to center of waste outlet(s)	20 7/8 (530)	20 7/8 (530)	20 7/8 (530)	20 7/8 (530)
Schedule 40 PVC drip pipe	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)	1 1/4 (32)
Refrigeration Outlet				
(G) Back of case to center of refrigeration outlet	16 1/8 (410)	16 1/8 (410)	16 1/8 (410)	16 1/8 (410)

Electrical Data

Number of Fans (12W)	4 ft	6 ft	8 ft	12 ft
8.25-in.	1	2	2	3

				Amperes				Watts			
Evaporator Fan				4 ft	6 ft	8 ft	12 ft	4 ft	6 ft	8 ft	12 ft
120V	50/60Hz	Energy Efficient		0.30	0.48	0.60	0.90	18	32	36	54
230V	50/60Hz	Energy Efficient		0.15	0.24	0.30	0.45	18	32	36	54
230V	60Hz	Export		0.33	0.60	0.66	0.99	50	96	100	150
230V	50Hz	Export		0.38	0.72	0.76	1.14	57	108	114	171

Minimum Circuit Ampacity (MCA)							
120V	50/60Hz	Energy Efficient		0.50	0.68	0.80	1.10
230V	50/60Hz	Energy Efficient		0.35	0.44	0.50	0.65
230V	60Hz	Export		0.53	0.80	0.86	1.19
230V	50Hz	Export		0.58	0.92	0.96	1.34

Maximum Over Current Protection (MOCP)							
120V				20	20	20	20
230V				15	15	15	15

Lighting

Only lighting configurations that are compliant with the U.S. Dept. of Energy (DOE) 2017 regulation are available for sale for use in the U.S.A.

				Amperes				Watts			
				4 ft	6 ft	8 ft	12 ft	4 ft	6 ft	8 ft	12 ft
LED LIGHTING											
Canopy Lights											
1 Row				0.16	0.26	0.36	0.54	19	31	43	64
Shelf											
None.											
Mullion											
60-in.				0.28	0.51	0.51	0.74	34	61	61	89

120V Lighting Circuit Total = Standard Lighting + Total Optional Lighting + Optional Shelf Lighting
230V Lighting Circuit Total = Multiply 120V Lighting Circuit Total by 0.52

S-Series SD6N
Dairy / Deli / Beverage /
Produce / Meat

ENDS or PARTITIONS

Each standard end and each insulated partition adds 1 1/2 in. (38 mm) to case line up. Optional view end with end bumper adds 3 3/4 in. (95 mm).

PHYSICAL DATA

Merchandiser Drip Pipe (in.)	1 1/4
Schedule 40 PVC	
Merchandiser Liquid Line (in.)	3/8
Merchandiser Suction Line (in.)	7/8

ESTIMATED SHIPPING WEIGHT †

Case	4 ft	6 ft	8 ft	12 ft	Solid End (each)
lb (kg)	530 (241)	925 (420)	1100 (499)	1500 (681)	75 (34)

† Actual weights will vary according to optional kits included.

Shelf Options

Approved shelf sizes for standard (horizontal, 3 position brackets) displays:

10-inch (3 position)
 12-inch (horizontal only)

Contact engineering for non-standard (4 position brackets or other) display recommendations.

Minimum number of Shelves: 4

Optimal number of Shelves: 5

Maximum number of Shelves: 8


Maximum number of Lighted Shelves: 0

Standard shelf complement for test purposes: (5) rows of 12 inch shelves, evenly distributed vertically.

Fan Wiring Offtime Defrost

S-Series **SD6N**
Dairy / Deli / Beverage /
Produce / Meat




1, 2 & 3 Fans



S-Series SD6N
Dairy / Deli / Beverage /
Produce / Meat

LED Canopy Light Circuits

LED Canopy Lighting — 1 Row



WARNING

All components must have mechanical ground, and the merchandiser must be grounded.

CIRCLED NUMBERS = PARTS LIST ITEM NUMBERS


R = Red Y = Yellow G = Green BL = Blue BK = Black W = White

● = 120V POWER ○ = 120V NEUTRAL ⏚ = FIELD GROUND ≡ = CASE GROUND

Optional Mullion Lighting LED Fixtures

S-Series SD6N
Dairy / Deli / Beverage /
Produce / Meat

LED Mullion Lighting



WARNING

All components must have mechanical ground, and the merchandiser must be grounded.

CIRCLED NUMBERS = PARTS LIST ITEM NUMBERS

R = Red Y = Yellow G = Green BL = Blue BK = Black W = White

● = 120V POWER ○ = 120V NEUTRAL ⚡ = FIELD GROUND $\overline{\text{mm}}$ = CASE GROUND

S-Series SD6N
Dairy / Deli / Beverage /
Produce / Meat



Scan the QR code with your mobile device to access additional product information or order parts.

Parts may also be ordered at:
parts.husmann.com
Call toll free: 1.855.487.7778

Revision History

Revision A: April 2020: Original Issue.

Revision B: June 2020: Updated cover logos.

Revision C: August 2020: Added cover warning.

Revision D: September 2023: Updated air gap on page 3.